## wattyl®



#### WATTYL **COLOURWOOD INTERIOR STAIN**

Wattyl Interior Stain is a semi-transparent, easy to use, pigment-based wood stain designed to produce a rich natural colouring and even toning on all timbers.

It penetrates into the timber to enrich and highlight the natural timber grain and texture. Wattyl Interior Stain is ideal for white wood and pine timbers and may be used on furniture, wall panelling, doors, window frames, skirting boards and kitchen cupboards. Not suitable for floors.

Liming White

Jarrah

English Mahogany

Traditional Cedar

American Redwood (Rimu)



Wenge

New Baltic Pine



Western Cedar



Nordic Teak



Walnut Brown

#### **Wattyl Colourwood Interior Stain**

Characteristics: A semi-transparent, easy to use pigment-based wood stain designed to produce a rich natural colouring and even toning on all timbers. It penetrates into the timber to enrich and highlight the natural timber grain and texture.

**Use on:** All interior timber such as louvre doors, woodwork, built-in furniture and timber panelling.

Apply with: Brush or cloth

Touch dry: 1 hour

**Recoat:** 4 hours

Clean up: Turps

Coverage: Up to 16m<sup>2</sup> per litre

No of coats: 1 coat



#### WATTYL **COLOURWOOD STAIN & VARNISH**

SATIN

Wattyl Stain & Varnish is a combined stain and clear finish. It offers the convenience of a single product finish instead of a dual stain and clear system.

Stain & Varnish is ideal for use on awkward areas, such as louvre doors, as it applies a stain and a clear finish at the same time, in one easy step. It is also suitable for use on most interior woodwork, built-in furniture and panelling. It is available in Satin finish.

#### 1 COAT APPLICATION



Liming White



Wenge



New Baltic Pine



New Golden Oak



Teak



New Maple

#### 2 COAT APPLICATION



Liming White



Wenge



New Baltic Pine



New Golden Oak





New Maple

#### **Wattyl Colourwood** Stain & Varnish Satin

Characteristics: A combined stain and clear finish which offers ease of use.

Use on: Most interior woodwork, louvre doors, built-in furniture and panelling

Apply with: Brush, applicator or spray gun

**Touch dry:** 4-6 hours

Recoat: 24 hours

Clean up: Turps

Coverage: Up to 12m<sup>2</sup> per litre

No of coats: 2-3 coats



1 COAT APPLICATION





Walnut

**2 COAT APPLICATION** 





Printed images may not be a true representation of the actual colour. Stain colour will appear different on different timbers.

Printed images may not be a true representation of the actual colour. Stain colour will appear different on different timbers.

#### WATTYL CRAFTSMAN **TINTABLE STAIN**

Wattyl Craftsman Tintable Stain is a semi-transparent, light fast stain suitable for interior and exterior use.

This product will not raise the grain, contains no wax and is suitable for use on all interior timbers. Wattyl Craftsman Tintable Stain is not a finish in itself and must be clear coated to achieve true colour, desired gloss level and protection. Apply Wattyl Estapol Interior Polyurethane or solvent based single pack Wattyl Estapol Moisture Cure Polyurethane. Also suitable for exterior use when overcoated with Wattyl Forestwood Exterior and Marine Varnish.



Seringa

Classic Teak

English Walnut

Liming Grey



Mission Brown



Colorado




Aged Oak





Liming Silver Birch

#### Wattyl Craftsman **Tintable Stain**



WATTYL

CRAFTSMAN' FINISH

CLEAR BASE 3 ML / 4 LTMS

**Use on:** Interior and exterior timber window frames, doors, skirting boards, balustrades, etc.

**Apply with:** Brush or cloth

Touch dry: 1 hour

Recoat: 6 hours. Allow the stain to dry overnight

Kauri

Ceda

Antique Walnut

Baltic Pine

before clear coating.

Clean up: Turps

Coverage: Up to 16m<sup>2</sup> per litre

No of coats: 1-2 coats



Rimu



Antique Cherry





Tallowwood



Smokey Haze





Liming Off White

#### Printed images may not be a true representation of the actual colour. Stain colour will appear different on different timbers.

#### WATTYL CRAFTSMAN **SANDING SEALER**

Wattyl Sanding Sealer is an interior, quick drying, pre-sanding sealer.

When applied to unfinished timber, it raises the grain resulting in easier sanding and aids the application of subsequent coats of Wattyl Estapol clear finishes. It effectively seals and fills the grain of unfinished timber surfaces such as built-in furniture, woodwork and panelling. It

can also be applied to timber previously stained with Wattyl Interior Stain.



#### **Wattyl Craftsman** Sanding Sealer

Characteristics: An interior, quick drying presanding sealer. When applied to unfinished timber it raises the grain resulting in easier sanding and aids the application of subsequent coats of Wattyl Estapol clear finishes.

Use on: Unfinished timber surfaces such as built-in furniture, woodwork and panelling. It can also be applied to timber previously stained with Wattyl Colourwood Interior Stain or Wattyl Craftsman Traditional Stain.

Apply with: Brush or spray gun

Touch drv: 1 hour

Recoat: 3 hours

Clean up: Turps

Coverage: Up to 16m<sup>2</sup> per litre

No of coats: 1 coat

#### WATTYL ESTAPOL **MOISTURE CURE POLYURETHANE**

HIGH GLOSS

Wattyl Estapol Moisture Cure Polyurethane is an extremely tough, durable, flexible and hard-wearing high gloss clear finish especially suited to timber, parquetry, cork, particle board and concrete flooring, particularly in heavy traffic areas.

#### WATTYL CRAFTSMAN **NATURAL TEAK OIL**

#### TRANSPARENT

#### Wattyl Natural Teak Oil

Teak Oil produces a natural oil finish on Teak and other timbers. It imparts a very smooth feel to the finish popular with Danish style furniture and interior teak timber surfaces. Use it as your final

WATTYL

Teak Oi

SCANDINAVIAN

coat over Estapol Matt as an oil finishing system on new timber or to rejuvenate an old piece of oiled timber.

#### Wattyl Craftsman Natural Teak Oil

Characteristics: Produces a natural oil finish on teak and other timbers. Recommended as a topcoat over Wattyl Estapol Polyurethane Matt. It is designed to impart a very smooth feel to the finish.

**Use on:** Final coat on clear coated timber or to rejuvenate previously oiled timber.

Apply with: Steel wool and cloth

Touch dry: 12 hours Recoat: N/A

Clean up: Turps

Coverage: Up to 20m² per litre

No of coats: 1 coat

#### **Wattyl Estapol Moisture Cure Polyurethane High Gloss**

Characteristics: An extremely tough, durable, flexible and hard-wearing high gloss clear finish.

Use on: Timber, parquetry, cork, particle board and concrete flooring. It is also suitable for application to surfaces such as timber furniture, skirting boards, doors, halls, bar tops and other areas subject to spillage.

**Apply with:** Brush, applicator or mohair roller

**Touch dry:** 2-4 hours Recoat: 6-24 hours

Clean up: Estapol Flooring 7008 Thinner then rinse in warm water

Coverage: Up to 5-10m<sup>2</sup> per litre

No of coats: 2-3 coats

#### WATTYL ESTAPOL WATER BASED XTRA CLEAR

SATIN AND GLOSS

Wattyl Estapol Interior Water Based Xtra Clear is a quick drying, low odour, clear finish designed for use on interior timber.

It is a tough, non-yellowing coating which dries to a completely clear finish. Wattyl Estapol Xtra Clear is suitable for interior timber wall panelling, joinery, doors, furniture, etc.

It is ideal for use on light coloured timbers such as Pine, Ash and Oak or over liming stain and other surfaces where the honey-tone of traditional varnishes is not desired. It is also suitable for use on MDF board.

Interior

Wattyl Estapol Xtra Clear has an opaque, milky appearance in the container and when first applied but dries to a completely clear finish. Estapol Xtra Clear is available in a gloss or satin finish.



**Characteristics:** A quick drying, low odour clear finish designed for use on interior timber. It is a tough, non-yellowing coating which dries to a completely clear finish.

**Use on:** Interior timber wall panelling, joinery, doors and furniture.

**Apply with:** Brush or applicator pad

Touch dry: 30 minutes

Recoat: 3 hours

Clean up: Water

Coverage: Up to 12m<sup>2</sup> per litre

No of coats: 2-3 coats

#### WATTYL ESTAPOL WATER BASED SPEED CLEAR

SATIN AND GLOSS

Wattyl Estapol Water Based Speed Clear is a tough, one pack, water based polyurethane finish which has been specifically designed to beautify, protect and preserve interior tongue and groove, parquetry and cork flooring.

Combining ease of application with quick drying properties, this water based floor finish enables timber and cork floors to be clear finished within a day. Wattyl Estapol Speed Clear has an abrasion resistant formulation which resists scratching and scuffing whilst highlighting the natural grain, colour and texture of the timber. Additionally, the exceptionally low odour of this product will ensure a more pleasant environment during application and while drying. It is available in a gloss and satin finish.



**Characteristics:** A tough one pack, water based polyurethane finish which has been specifically designed to beautify, protect and preserve flooring.

**Use on:** Interior tongue and groove, parquetry and cork flooring.

Apply with: Brush or applicator

**Touch dry:** 30 minutes

Recoat: 3 hours

Clean up: Water

Coverage: 10-16m<sup>2</sup> per litre

No of coats: 2-3 coats

### WATTYL ESTAPOL POLYURETHANE

MATT, SATIN AND GLOSS

## Interior Wattyl Estapol Polyurethane is a clear finish designed for use on interior timber surfaces.

It is a tough, durable finish which is resistant to wear, normal household chemicals and moderate heat. It produces a warm honey tone on timber. Interior Estapol Polyurethane is suitable for furniture, doors, windows and skirting boards. It is touch dry in 2-3 hours and can be recoated in 8 hours.

It is available in a matt, satin and gloss finish as well as an aerosol which is ideal for small or intricate timber objects and surfaces.



**Characteristics:** A clear finish designed for use on all interior timber surfaces. It is extremely tough, durable finish resistant to wear, normal household chemicals and moderate heat.

**Use on:** May be used on tables, panelling, furniture, doors and skirting boards. Estapol Gloss and Satin may also be used on low traffic floors.

Apply with: Brush, applicator or spray gun

Touch dry: 2-3 hours

Recoat: 8 hours

Clean up: Turps

Coverage: Up to 16m<sup>2</sup> per litre

No of coats: 2-3 coats

## WATTYL ESTAPOL OIL MODIFIED POLYURETHANE

SATIN AND GLOSS

Wattyl Estapol Oil Modified Polyurethane is a tough, durable, wear resistant polyurethane coating for use on timber and parquetry floors.

Wattyl Estapol Oil Modified Polyurethane is easy to apply and provides a clear finish which enhances and highlights the timber's natural grain and warmth. Estapol Oil Modified Polyurethane is particularly suited for use on new timber floors commonly prone to shrinkage to reduce the risk of edge gluing.

Wattyl Estapol Oil Modified Polyurethane provides a durable finish that resists cracking and chipping and is easily maintained and repaired. It is ideally suited for use on most types of domestic timber and parquetry flooring as well as floors subjected to heavy traffic, such as community halls, factories, public buildings and gymnasiums etc. Estapol Oil Modified Polyurethane is also suitable for use on most interior woodwork, such as built-in-furniture, skirting boards and panelling. It is available in a gloss and satin finish.

#### Wattyl Estapol Oil Modified Polyurethane Satin & Gloss

**Characteristics:** A tough, durable, wear resistant polyurethane. Easy to apply and provides a clear, contemporary finish which enhances and highlights the timbers natural grain and warmth. Reduces the risk of edge bonding.

**Use on:** Most types of domestic timber and parquetry flooring, as well as floors subjected to heavy traffic such as community halls, factories, public buildings and gymnasiums.

**Apply with:** Brush, applicator or mohair roller

Touch dry: 2 hours

Recoat: 12 hours

Clean up: Turps

Coverage: Up to 10m<sup>2</sup> per litre

No of coats: 2-3 coats

6 giosa and satiri mish.

# Don't worry, it's Wattyl

Whatever you need, we can help.



